

## Technistream 50l (and 20l) Compressed Air Pressure Foaming Machine

The Technistream 50/20 is a compressed air driven foaming machine for the application of cleaning chemicals in the food, pharmaceutical and agricultural industries.

The tank is pressurised by the compressed air and delivers the pre-diluted chemical to the application hose. Compressed air is added to create a dense dry foam. Foam quality is fully adjustable to suit the chemical and the application.

### FEATURES:

- Robust, hygienic, all stainless steel construction
- Simple operation, no moving parts
- Low maintenance
- Different hose colours available (Blue, Red, Green, Yellow)
- 316 stainless steel tank
- CE Pressure Equipment Directive (PED) (2014/686EU) compliant tank

### ORDERING INFORMATION:

	<b>50L</b>	<b>20L</b>
Blue Hose	0715	0714
Red Hose	0715R	0714R
Green Hose	0715G	0714G
Yellow Hose	0715Y	0714Y

Note: These units may need to be annually inspected or tested. Please check your site regulations.



### TECHNICAL DETAILS:

- Tank capacity 50l or 20l
- Max working pressure: 6bar
- Air supply: approx. 10 m<sup>3</sup> /h (150 l/min)
- Approx. solution flow rate @ 4bar pressure: 3l/min
- Standard hose length: 10m
- Weight: 27kg